



Static Dissipative PVC Shoe

2301 Series

PPM-S001

Physical Properties

Material Type	PVC	
Production Type	Direct Injection Moulding	
Logo	T.H.I.S / Professional / Oil Resistance / Non Slip	
Available Size (mm)	230, 240, 250, 260, 270, 280, 290, 300	
Weight	800 +/- 100	grams/pair
Surface Resistivity (Bottom Sole)	$10^6 - 10^9$	ohms/sq
Resistivity (RTG)	$10^5 - 10^8$	ohms
Color	Upper Cover	White
	Bottom Sole	Gray
Materials	Upper Cover	Wet PU 1.5mm + Non-woven 0.9mm (T) + ESD Tricot
	Taping	Wet PVC 0.4mm (T) + 15mm (W)
	Inner Sole	Polyester + Black Conductive Thread
	Bottom Sole	PVC injection with ESD Compound
	Thread	All round for Better enforce
Application	ESD Control Heavy Duty Working Area	

6 July 2010 (PR09)



Pro-Pack Materials Pte Ltd

The ESD & Cleanroom Specialist



2301 Series S001

6 July 2010 (PR09)

Pro-Pack Materials Pte Ltd (HQ)
Pro-Pack Materials (Wuxi) Co., Ltd
Pro-Pack Materials (Philippines) Inc.
Pro-Pack Materials India Pvt Ltd

Bold Pack Industries Sdn Bhd
Bold-Pack Materials (Thailand) Co. Ltd
PT Pro-Pack Industries

No. 2, #08-05, Bukit
Batok St 23, Bukit Batok
Connection, Singapore
659554

T : +65-63541511
F : +65-63541711
E: sales@pro-pack.com.sg
W : www.pro-pack.com.sg