



**ESD Safety Shoe  
PPM-2009GW  
2307 Series**

Specification				
Grey Sole + White PU Leather (For Safety Booties)				
Materials	Upper Cover	PU (Polyurethane / Leather)		
	Toe	Steel Toe (200J Impact & 15 KN Compression)		
	Bottom Sole	PU Injection mould with ESD compound		
Application	ESD Control Heavy Duty Working Area			
Oil Resistant, Anti-Puncturing	Meet EN ISO 20345 : 2011 Standard			
Size	220, 230, 240, 250, 260, 270, 280, 290 mm			
Weight	1000	Size 270mm		Grams / Pair
Resistive Characteristic	Point to Groundable point	$10^6 - 10^8$	Ohm	ANSI ESD STM 9.1, TR 53 Compliance Verification
	Footwear and Flooring system	$10^6 - 10^8$	Ohm	ANSI ESD STM 97.1
		< 100	V	ANSI ESD STM 97.2
Static Decay	5k – 0.5k	<0.5 Sec		
Washing Requirement				
Washing Temperature	40	Degree		
Drying Temperature	< 70	Degree		

Reorder Code

2307-0001	220
2307-0002	230
2307-0003	240
2307-0004	250
2307-0005	260
2307-0006	270
2307-0007	280
2307-0008	290
2307-0009	300

15 November 2018 (PR09)



PPM-2009GW