

Product Data

Mat, Conductive
Anti-Fatigue

Code : 5318 Series



	Properties	Units	Specification	
Basic Properties	Material	-	Conductive NBR + High Elastic Polyurethane Foam	
	Colour	-	Black	
	Weight	kg	3.4	2.1
	Length	Cm	90 +/- 1%	45 +/- 1%
	Width	Cm	60 +/- 1%	
	Thickness	mm	16	
	Mechanical	Intensity	Sh-A	30 ~ 40
Density		Kg/cubic meter	-	-
Compressibility		%	50	
Degree of Abrasion		cubic mm	180	
Tensile Strength		Mpa	1.5	
Elongation		%	500	
Crushing Strength		N/mm	4	
Stability (Anti-slip)		R/V	10/11	
Electrical Resistance	Surface	Ohm	10E5 ~ 10E6	
	Heat	The Lowest Point for use	° C	80
Available highest point		° C	120	
Others	Available	-	Class 100 Cleanroom	

Pro-Pack Materials Pte Ltd

Blk 970, Toa Payoh North, #04-18
Toa Payoh Industrial Estate
Singapore 318992

Tel : +65 63541511
Fax : +65 63541711
Email : sales@pro-pack.com.sg
Website : www.pro-pack.com.sg

Regional Offices :

Malaysia

Bold Pack Industries Sdn Bhd

Indonesia

PT Pro-Pack Industries

Thailand

Bold-Pack Materials (Thai) Co. Ltd

Philippines

Pro-Pack Materials (Philippines) Inc.

India

Pro-Pack Materials India Pvt Ltd

China

Pro-Pack Materials (Wuxi) Co., Ltd