

Product Data

Tray, PP, Conductive

Code : 6902-0001



Mechanical Properties	Specification	Units	ASTM Method
Tensile Yield Strength	≥ 20	Mpa	D-638
Elongation @ break	≥ 10	%	D-638
Flexural Strength	≥ 20	Mpa	D-790
Flextural Modulus	≥ 800	Mpa	D-790
Notched Izod Impact Strength @23 °C	≥ 350	J/m	D-256

Electrical Properties

Volume Resistivity	≤ 1 x 10 ⁵	Ω-cm	D-257
Surface Resistivity	≤ 1 x 10 ⁵	Ω	D-257

Pro-Pack Materials Pte Ltd

Blk 970, Toa Payoh North, #04-18
Toa Payoh Industrial Estate
Singapore 318992

Tel : +65 63541511
Fax : +65 63541711
Email : sales@pro-pack.com.sg
Website : www.pro-pack.com.sg

Regional Offices :

Malaysia

Bold Pack Industries Sdn Bhd

Indonesia

PT Pro-Pack Industries

Thailand

Bold-Pack Materials (Thai) Co. Ltd

Philippines

Pro-Pack Materials (Philippines) Inc.

India

Pro-Pack Materials India Pvt Ltd

China

Pro-Pack Materials (Wuxi) Co., Ltd