

Product Data

Sheet, Gerflor Commercial Flooring

Code : 7002 Series

Miplolam Troplan Plus is a flexible homogenous calendered compacted flooring covering in sheet, with directional design, colour dyed as a raw mixture to ensure even colour throughout the thickness. Its surface is densely compacted for improved wear and ease of maintenance. It receives a Polyurethane reinforce (PUR) surface treatment for ease of maintenance and to avoid the use of an acrylic emulsion after installation.

Miplolam Troplan Plus is Anti-bacterial and fungicidal.

The flooring complies with the EN 649 (34 - 43) and has a K5 (Group P) wear rating. It is suitable for heavy traffic areas.

Installation

Installation should be carried out in accordance with local standards, subfloor to be smooth, hard, clean and dry prior to laying. Where applicable the subfloor must incorporate an effective Damp Proof Membrane. The material must be allowed to acclimatize 24 hours before installation in a room temperature of between 18 - 24 °C.

Maintenance

Maintenance should be carried out regularly to retain the appearance and durability of the floor. The floor covering should be maintained with regular sweeping and damp mopping using a neutral cleanser, more intense cleaning should be carried out using a fine spray cleaning pad under a floor machine, or for larger areas combined machine cleaning.

Further installation and maintenance instruction are available upon request.

Pro-Pack Materials Pte Ltd

Blk 970, Toa Payoh North, #04-18
Toa Payoh Industrial Estate
Singapore 318992

Tel : +65 63541511
Fax : +65 63541711
Email : sales@pro-pack.com.sg
Website : www.pro-pack.com.sg

Regional Offices :

Malaysia

Bold Pack Industries Sdn Bhd

Indonesia

PT Pro-Pack Industries

Thailand

Bold-Pack Materials (Thai) Co. Ltd

Philippines

Pro-Pack Materials (Philippines) Inc.

India

Pro-Pack Materials India Pvt Ltd

China

Pro-Pack Materials (Wuxi) Co., Ltd

Product Data

Sheet, Gerflor Commercial Flooring

Code : 7002 Series

Pro-Pack Materials Pte Ltd

Blk 970, Toa Payoh North, #04-18
Toa Payoh Industrial Estate
Singapore 318992

Tel : +65 63541511
Fax : +65 63541711
Email : sales@pro-pack.com.sg
Website : www.pro-pack.com.sg

Regional Offices :

Malaysia
Bold Pack Industries Sdn Bhd

Indonesia
PT Pro-Pack Industries

Thailand
Bold-Pack Materials (Thai) Co. Ltd

Philippines
Pro-Pack Materials (Philippines) Inc.

India
Pro-Pack Materials India Pvt Ltd

China
Pro-Pack Materials (Wuxi) Co., Ltd

Description

Total thickness	EN 428	mm	2
Weight	EN 430	g/m ²	3100
Width / Length of sheet	EN 426	cm/lm	200 / 20

Classification

European	EN 685 / EN 649	-	34 - 43
K Rating	-	Class	K5
Fire Rating	EN 13 501 - 1	-	Bfl
	DIN 4102	-	B 1
	GB 8624 - 2006	-	GB 8624 Bf1-s1
Toxic Testing	GB 18586 - 2001	-	Good
Electrical Resistance	EN 1815	Kv	< 2
Slip Resistance Dry	pr EN 13893	-	≥ 0.3
Slip Resistance Wet	DIN 51130	-	R 9

Performances

Abrasion Resistance	EN 660.1	mm	< 0.15
Abrasion Group	-	-	P
Dimensional Stability	EN 434	%	Sheet ≤ 0.4
Indentation	EN 433	mm	≈ 0.03
Thermal Conductive	EN 12 524	W/(m.k)	≈ 0.25
Colour Fastness	EN 20 105 - B02	-	≥ 6
Chemical Products Resistance	EN 423	-	Good
Anti-Bacterial and Fungicidal Treatment	EN ISO 846	-	YES
Wear layer Treatment	-	-	PUR
Colour Number	-	-	18