

## Product Data

**Bag, Tyvek Moisture  
Barrier**

**Code : 1004 Series**



### Material Construction

Tyvek	170 +/- 60 Micron
LDPE	25 Micron
Aluminum Foil	7 Micron
LDPE	25 Micron
LLDPE	80 Micron
Antistatic Coating	

### Physical Properties

Tensile Strength	Width	445	Kg / cm <sup>2</sup>	KS M 3001-91
	Length	357	Kg / cm <sup>2</sup>	KS M 3001-91
Elongation	Width	41.2	%	KS M 3001-91
	Length	30.7	%	KS M 3001-91
Surface Resistivity	INNER	10 <sup>9-12</sup>	Ω / sq	LCD Mega ohm meter Item A 50070
	OUTER	10 <sup>9-11</sup>	Ω / sq	LCD Mega ohm meter Item A 50070
Permeability		0.00047	g / sqin / 24hr	KS A 1013-91
Seal Strength		3.17	Kgf / 15mm	KS A 1512-96
Punch Strength		2.61	Kgf	JAS 1019
Thickness		307	Microns ± 60 Microns	

#### Pro-Pack Materials Pte Ltd

Blk 970, Toa Payoh North, #04-18  
Toa Payoh Industrial Estate  
Singapore 318992

Tel : +65 63541511  
Fax : +65 63541711  
Email : sales@pro-pack.com.sg  
Website : www.pro-pack.com.sg

Regional Offices :

**Malaysia**  
Bold Pack Industries Sdn Bhd

**Indonesia**  
PT Pro-Pack Industries

**Thailand**  
Bold-Pack Materials (Thai) Co. Ltd

**Philippines**  
Pro-Pack Materials (Philippines) Inc.

**India**  
Pro-Pack Materials India Pvt Ltd

**China**  
Pro-Pack Materials (Wuxi) Co., Ltd