

## Product Data

**Shoe Safety White Static  
Dissipative**

**Model : TAU - 9326**

**Code : 2302 Series**



### Pro-Pack Materials Pte Ltd

Blk 970, Toa Payoh North, #04-18  
Toa Payoh Industrial Estate  
Singapore 318992

Tel : +65 63541511  
Fax : +65 63541711  
Email : sales@pro-pack.com.sg  
Website : www.pro-pack.com.sg

Regional Offices :

**Malaysia**  
Bold Pack Industries Sdn Bhd

**Indonesia**  
PT Pro-Pack Industries

**Thailand**  
Bold-Pack Materials (Thai) Co. Ltd

**Philippines**  
Pro-Pack Materials (Philippines) Inc.

**India**  
Pro-Pack Materials India Pvt Ltd

**China**  
Pro-Pack Materials (Wuxi) Co., Ltd

### Physical Properties

Material Type	PU (Polyurethane) / Artificial Leather		
Production Type	Direct Injection Moulding		
Logo	Professional / Oil Resistance / Non Slip		
Available Size (mm)	225, 230, 240, 250, 260, 270, 280, 290, 300		
Weight	800 +/- 100		grams/ pair
Surface Resistivity (Bottom Sole)	$10^6 - 10^8$		ohms/sq
Resistivity (RTG)	$10^5 - 10^7$		ohms
Static Decay	5k – 0.5k	Less than 0.2 second	sec
Color	Upper Cover	White	
	Bottom Sole	White	
Materials	Upper Cover	Wet PU 1.5mm + Non-woven 0.9mm (T) + Merry Mesh Lining	
	Taping	Wet PU 0.4mm (T) + 15mm (W)	
	Enforced Plastic Toe Cap	S50C 1.3mm (T) PSB Approved	
	Inner Sole	Polyester	
	Bottom Sole	PU injection with ESD Compound	
Enforce Plastic Toe Cap Test (KS G-3127-99)		102 – 2 (S50C) Pressure Resist : 2.6mm / 2 +/-	
Application	ESD Control Heavy Duty Working Area		