

Product Data

**Fabric, Diamond
Conductive (V361)**

Model : PPM - 150

Code : 3603 Series

Pro-Pack Materials Pte Ltd

Blk 970, Toa Payoh North, #04-18
Toa Payoh Industrial Estate
Singapore 318992

Tel : +65 63541511
Fax : +65 63541711
Email : sales@pro-pack.com.sg
Website : www.pro-pack.com.sg

Regional Offices :

Malaysia
Bold Pack Industries Sdn Bhd

Indonesia
PT Pro-Pack Industries

Thailand
Bold-Pack Materials (Thai) Co. Ltd

Philippines
Pro-Pack Materials (Philippines) Inc.

India
Pro-Pack Materials India Pvt Ltd

China
Pro-Pack Materials (Wuxi) Co., Ltd

Physical Properties

Yarn	Warp	75	Denier	
ECF	Warp	F-901 Diamond	BASF	
Weight		165	g/m ²	
Weave	Warp ————— 4 Weft		Bar Net	
Density	Warp	32W	Threads / Inch	
	Weft	45C	Threads / Inch	
Dimension	Warp / Weft	58" / 60" x 45 / 60	Inch x yd	
Surface Resistivity		10 ⁵ - 10 ⁶	Ohm / sq	ASTM-D257
Static Decay	5000 - 500 V	< 0.01	Sec	FTS M4046 S101C
Fraction Static Voltage		< 50	V	JIS-L1094B

Data represents actual test results and is not intended to serve as a product specification