

Product Data

Tile, Normal StaticFlor

Code : 7002 Series

Pro-Pack Materials Pte Ltd

Blk 970, Toa Payoh North, #04-18
Toa Payoh Industrial Estate
Singapore 318992

Tel : +65 63541511
Fax : +65 63541711
Email : sales@pro-pack.com.sg
Website : www.pro-pack.com.sg

Regional Offices :

Malaysia
Bold Pack Industries Sdn Bhd

Indonesia
PT Pro-Pack Industries

Thailand
Bold-Pack Materials (Thai) Co. Ltd

Philippines
Pro-Pack Materials (Philippines) Inc.

India
Pro-Pack Materials India Pvt Ltd

China
Pro-Pack Materials (Wuxi) Co., Ltd

Features

Sanitized treatment, strong antibacterial function

Dimensional stability, adopting the special glass fiber

Good sound insulation: 18dB

Excellent stain resistance and easy cleaning, special iodine proof function

Fire resistance: 0.58KM/m²

No need for initial polishing, UV coating

Technical Data	Standards	BS	BF	
Classification	EN685	Classes	Classes	
	Commercial	32	33	
	Industrial	41	41	
	UPEC	U3 P2 E2/3 C2	U3 P3 E2/3 C2	
Total Thickness	EN428	2.00mm	2.60mm	3.00mm
Wear layer thickness	EN429	0.5mm	0.5mm	0.7mm
Total weight	EN430	3000g/m ²	2300g/m ²	3000g/m ²
UV treatment		Yes		
Abrasion group	EN660-1	Group T:≤0.08		
Residual indentation	EN433	0.15mm		
Furniture leg	EN424	No damage		
Castor Chair	EN425	No damage		
Dimensional stability	EN434	≤0.1%		
Reaction to fire	EN13501-1	Bf1-S1		
	GB8624-1997	Bf1-S1		
Slip resistance	DIN	R9		
Impact sound reduction	ENISO-140-8	8db	17db	18db
Light fastness	ENISO 105-B02	≥7		
Chemical resistance	EN423	High resistance		
Resistance to bacteria	NF EN ISO 846	Grade 1		
Thermal resistance	EN12524	0.25m ² K/W		
Under-floor heating		Suitable		
Form of delivery	EN426	20lm	12lm	15lm