

## PRODUCT INFORMATION

|                            |                                                                                        |
|----------------------------|----------------------------------------------------------------------------------------|
| <b>Product Description</b> | Static Dissipative PU Shoe                                                             |
| <b>Product Code</b>        | 2012-0030, 2012-0032, 2012-0034, 2012-0036, 2012-0038, 2012-0040, 2012-0042, 2012-0043 |

## WEIGHT

|                                              |
|----------------------------------------------|
| 435 - 485 Grams/pair (+/- 50 Grams per size) |
|----------------------------------------------|

## STATIC DECAY TIME

|                               |
|-------------------------------|
| Less than 0.1 second (5KV-0V) |
|-------------------------------|

## PHYSICAL DIMENSIONS

|                     |                  |                  |                  |                  |
|---------------------|------------------|------------------|------------------|------------------|
| <b>Product Code</b> | <b>2012-0030</b> | <b>2012-0032</b> | <b>2012-0034</b> | <b>2012-0036</b> |
| <b>Size</b>         | 220mm            | 230mm            | 240mm            | 250mm            |
| <b>Product Code</b> | <b>2012-0038</b> | <b>2012-0040</b> | <b>2012-0042</b> | <b>2012-0043</b> |
| <b>Size</b>         | 260mm            | 270mm            | 280mm            | 290mm            |

## MATERIALS AND DESIGN

|                        |                                                                                                                                                                                     |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Production Type</b> | Direct Injection Moulding                                                                                                                                                           |
| <b>Outer Sole</b>      | PU (Polyurethane) + Antistatic Agent                                                                                                                                                |
| <b>Inner Sole</b>      | Polyester with Bio-Dots + Latex Sponge + T/C Fabric                                                                                                                                 |
| <b>Upper Cover</b>     | <ol style="list-style-type: none"> <li>Outer Layer - PU (Polyurethane) Laminated</li> <li>Middle Layer - PU (Polyurethane) Foam</li> <li>Inside Layer - Non Woven Fabric</li> </ol> |
| <b>Others</b>          | Sewing thread made of filament yarn                                                                                                                                                 |

## PHYSICAL PROPERTIES

|                          |                  |
|--------------------------|------------------|
| <b>Volume Resistance</b> | 10e6 - 10e8 ohms |
|--------------------------|------------------|

## APPLICATION

|                                                                           |
|---------------------------------------------------------------------------|
| Electrostatic Control at indoors for any clean environmental working area |
|---------------------------------------------------------------------------|



### CUSTOMER ACKNOWLEDGEMENT

| Version | Revision Date | Pro-Pack Sales PIC<br>(Name/ Signature) | Customer Acknowledgement<br>(Name/ Signature) |
|---------|---------------|-----------------------------------------|-----------------------------------------------|
| A       | 03 Oct 2024   |                                         |                                               |