

PRODUCT INFORMATION

Product Description	Static Dissipative Piping Fabric
Product Code	3618-0001
Packing	25rolls/ctn
Colour Code	MDF-160CO
Colour	White
Recommended Storage Condition	Avoid ultraviolet (UV)-light exposure, keep away from direct sunlight and keep dry
Precautions	Cleaning with mild detergent



PHYSICAL SPECIFICATION

No	Items	Specification	Tolerance
A	Width	34mm	±2mm
B	Length	200m	±20m
C	Grid size	5mm x 5mm	±0.5mm

CHARACTERISTIC

No	Items	Specification	Unit
A	Surface Resistance (35±5% RH, 20±2°C)	1.0E06≤R<1.0E09	Ω
B	Surface Resistance After Wash 50 Times (Clean With Mild Detergent Under 70°C)	1.0E08≤R<1.0E09	Ω
C	Heat Resistance	Up to 70°C	°C
D	Yarn	Warp: 100D Weft: 100D	Denier
E	Density	Warp: 165 (±5) Weft: 80 (±5)	Thread/inch
F	Weave	2/1 twill (5mm grid)	-
G	Friction Static Voltage	<300	V

MATERIAL SPECIFICATION

Composition
98% of Polyester Yarn + 2% of Carbon Yarn

CUSTOMER ACKNOWLEDGEMENT

Version	Revision Date	Pro-Pack Sales PIC (Name/ Signature)	Customer Acknowledgement (Name/ Signature)
A	13 May 2022		