

# GZ-1800-H: Network Router

## of GZ-1800 ULV ESD Monitor



**GZ-1800-H** is a dedicated network router to be used with a GZ-1800 **proactive** ULV ESD monitor. It has 4 connection ports each of which can connect to a maximum of 32 GZ-1800 monitors. A maximum of 128 monitors can be connected to this Router. The Router contains an RJ45 port that can connect to a LAN through TCP/IP. A special high speed processing technique is used in the Router to provide high performance data processing and communication amongst networked monitors and the host PC-based network management software.



**SPECIFICATIONS:**

Key Functions:	<ul style="list-style-type: none"><li>☑ x4 RJ11 ports for RS-485 daisy-chain inter-connection among monitors</li><li>☑ Each RJ11 connection port supports connection up to 32 monitors</li><li>☑ x1 RJ45 connection port for TCP/IP link to Local Area Network (LAN)</li><li>☑ Automatic connection detection; Independent hardware operation</li><li>☑ Support wireless LAN connection</li></ul>
LED:	x 6 tricolor LED
Power:	9~12V DC, 1A
Mechanical:	L: 4 inch    W: 3 inch    H: 1 inch

**MEGALIN** Megalin Source International

• Address 3F-6 No.81 Sec.1 Xintai 5th Road, Xizhi District, New Taipei City 22101, TAIWAN  
• Tel +886-2- 8698-4181 (Main) • Fax +886-2-8698-4197 • E-mail : sales@megalinsource.com  
China Offices : • Shenzhen : +86-755-2774-6923 • Kunshan/Suzhou : +86-512-5519-7252

(©2011Megalín Source International. All Rights Reserved.)

v.2204



Distributed by

**Pro-Pack Materials Pte Ltd**  
The ESD & Cleanroom Specialist

• No. 2, Bukit Batok Street 23, #08-05 Bukit Batok Connection, Singapore 659554.    ✉ sales@pro-pack.com.sg    ☎ (65) 6354 1511