

Marketing Specification

PRODUCT INFORMATION

| Product Description | Floor Mark Tape Yellow Logo | |
|----------------------------|-----------------------------|--|
| Product Code | 5206-0043 | |
| Size | 50mm x 33m | |

DESCRIPTIONS

PET laminated tape with ESD symbol and "ESD Protected Area" printings

FEATURES

- ESD properties on both surfaces
- Printing will not be removed easily thanks to PET laminating
- Compatible with floor cleaners
- Abrasion resistant
- Heavy duty
- Plastic core for less particles

PHYSICAL PROPERTIES

| Properties | Unit | Values | Test Method |
|------------------------------------|--|---------------------|---------------|
| Film | | PET + PVC | |
| Adhesive Type | 1 | Anti-Static Acrylic | |
| Film Thickness | mm | 0.115 ± 0.005 | ASTM D1000 |
| Total Thickness | mm | 0.145 ± 0.05 | |
| Strength of Adhesive | gf/in | 500 over | |
| Surface Resistance (both sides) | Ω | 10e7-9 | ASTM D 257 |
| Electrostatic Discharge | sec | 0.1 under | 7.01111.5.237 |
| Constructions | Antistatic treatment PET Film(15µm) Printed PVC Film(ESD symblo and "ESD Protected Area") (100) Antistatic treatment Antistatic acrylic adhesive(30µm) | | |

Rev.A, **Effective Date**: 09th-Oct-2024



CUSTOMER ACKNOWLEDGEMENT

| Version | Revision Date | Pro-Pack Sales PIC (Name/ Signature) | Customer Acknowledgement (Name/ Signature) |
|---------|---------------|---|--|
| A | 09 Oct 2024 | | |