

PRODUCT INFORMATION

Product Description	ESD Scanner
Packing	1pc/box
Product Code	5396-0053
Model Number	PPM 5004
Material Colour	Black
Recommended Storage Condition	Temp 20 °C ~40 °C, Humidity <80%



PHYSICAL SPECIFICATION

No	Items	Specification	Tolerance
A	Length	105mm	±3mm
B	Width	70mm	±3mm
C	Height	170mm	±3mm
D	Cable Length	1800mm	±20mm

CHARACTERISTIC

No	Item	Specification
1	CPU	32 bits
2	Scanning speed	300 times/second
3	Button life	5000,000 times
4	Light source	Laser diode –wave length 650 nm
5	Depth of focus	EAN-13(13mil) 55-150mm Code39(5mil) 45-80mm Code128(15mil) 35-60mm
6	Manual scanning mode	YES
7	Scanning mode	One Dimensional Mode (EAN13, EAN8, UPCA, UPCE, Code128, Code39, Codabar, UCC/EAN128, RSS, ITF14, ITF16, Standard25, Matrix25, COOP25, industrial 25, Plessey, Code11, Code93 etc.)
8	Scanning accuracy	≥4mil
9	Scanning angle	Pitch ±50° Tilt 35° Skew 55°
10	Print contrast signal	≥30%
11	Port	USB,RS232,P±S/2
12	Alarm mode	Buzzer, indicator
13	Voltage	5V DC±5%
14	Electricity@5VDC	Operation current 65mA Standby current 5mA
15	Operation temperature	-20 °C to +60 °C
16	Electrostatic Protection	±14kv (air discharge), ±8kv (direct discharge)
17	Protection Grade	IP54
18	Surface Resistance	1.0E04≤R<1.0E09

MATERIAL SPECIFICATION

No	Item	Material/ Type
1	Scanner	Acrylonitrile Butadiene Styrene (ABS) with Coating Antistatic
2	Cable	Rubber & Copper
3	ESD Logo	Stick on the scanner

CUSTOMER ACKNOWLEDGEMENT

Version	Revision Date	Pro-Pack Sales PIC (Name/ Signature)	Customer Acknowledgement (Name/ Signature)
C	27 Sep. 2023		