



# Outlet Tester with Qube & Ground Cord PGT-6302QG

## Data Sheet

### Provides an ESD ground path to a previously tested receptacle

The Prostat Qube™ replaces expensive electrical ground circuit testers and indicators with a convenient, cost effective means to connect vital ESD controls to grounded electrical outlets. Use the Qube to ground workstations, mats, wrist strap testers, instruments, and other ESD products to an approved pre-tested facility electrical ground.

The Prostat PGC-015G is a 15 foot straight common point ground cord with two banana receptacles, in low profile housing for connecting two wrist straps. The PGC-015G includes one 1.0x106 ( $\pm 20\%$ ) current limiting resistor molded in the snap housing, a low profile housing with a 10 mm male snap for easy connection to mat, a male banana plug for cord connection to ground.

Tests standard 3-wire and GFCI protected 120V outlets for 7 common wiring errors. GFCI function tests GFCI and standard outlets wired in series with GFCI outlets (e.g. multiple outlets in kitchen or bath). Neon lamps indicate 7 common wiring conditions with the wiring condition legend easily visible on top and bottom of tester. Tester offers a compact ergonomic design with over-molded rubber grips.



Distributed by

**Pro-Pack Materials Pte Ltd**  
The ESD & Cleanroom Specialist

No. 2, Bukit Batok Street 23, #08-05 Bukit Batok Connection, Singapore 659554.

sales@pro-pack.com.sg

(65) 6354 1511



Data Sheet

Specifications for the Q007 ESD Ground Cube

Dimensions	
Length (in / cm)	1.25 / 3.175
Width (in / cm)	1.0 / 2.54
Depth (in / cm)	1.0 / 2.54
Weight (oz / g)	0.6 / 15
Physical Properties	
Case Material	Fire Retardant ABS
Color	Green
Configuration	2 standard banana jack inputs, Brass Grounding Pin, 2 FR ABS Spades

Specifications for the PGC-015G Green 15 Foot Ground Cord

Dimensions	
Length (ft / meters)	15 / 4.6
Resistor	
One megohm ( $\pm 10\%$ ) resistor molded into snap connection	
Physical Properties	
Color	Green

Specifications for the Sperry GFI6302 GFCI Outlet Tester

Operation Range	
120 VAC, 60 Hz; CAT III 300V	
Indicators	
Visual Only	
Operating Environment	
32° - 104° F (0 - 32° C) 80% RH max., 50% RH above 30° C	

1072 Tower Lane, Bensenville, IL 60106 USA  
Phone +1 (630) 238-8883 Fax +1 (630) 238-9717

[www.prostatcorp.com](http://www.prostatcorp.com)

©2014 Prostat Corporation. All rights reserved. Prostat, Prostat Corporation, Qube and the Prostat logo are trademarks or registered trademarks of Prostat Corporation or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. Complying with all applicable copyright laws is the responsibility of the user. Prostat reserves the right to change, without notice, product offerings or specifications. Printed in U.S.A. REV1: 7/25/12



Distributed by

**Pro-Pack Materials Pte Ltd**  
The ESD & Cleanroom Specialist

No. 2, Bukit Batok Street 23, #08-05 Bukit Batok Connection, Singapore 659554. [sales@pro-pack.com.sg](mailto:sales@pro-pack.com.sg) (65) 6354 1511