



Grounding Set - Metal Cuff

PWS-661M

Data Sheet

Grounding Set with Metal Wrist Strap

The PWS-620 Wrist Strap features a metal wristband that incorporates a patented linking system. It enables you to adjust the strap to fit virtually any wrist size. This unique band comes manufactured in 130mm lengths and can be easily enlarged using one or more of the five 10mm nylon expansion links included. The band is extremely comfortable, as each one is “custom fit” to the user. This band eliminates the need to stock bands of various sizes.

The Prostat Qube™ replaces expensive electrical ground circuit testers and indicators with a convenient, cost effective means to connect vital ESD controls to grounded electrical outlets. Use the Qube to ground workstations, mats, wrist strap testers, instruments, and other ESD products to an approved pre-tested facility electrical ground.

The Prostat PGC-015G is a 15 foot straight common point ground cord with two banana receptacles, in low profile housing for connecting two wrist straps. The PGC-015G includes one 1.0x106 ($\pm 20\%$) current limiting resistor molded in the snap housing, a low profile housing with a 10 mm male snap for easy connection to mat, a male banana plug for cord connection to ground.



Distributed by

Pro-Pack Materials Pte Ltd

The ESD & Cleanroom Specialist

No. 2, Bukit Batok Street 23, #08-05 Bukit Batok Connection, Singapore 659554.

sales@pro-pack.com.sg

(65) 6354 1511



Data Sheet

Specifications for the PWS-620 Metal Band Wrist Strap

Cuff Assembly	
Construction	Made from jewelry quality stainless steel, tested to MIL STD 202 Method 101.
Thickness	3.5mm, average weight 33 grams Manufactured to 130mm circumference with 5 10mm nylon expansion links.
Electrical Properties	Outer band: insulative at 500V per unit mm, coating is polyurethane based polymer Inner band: Conductive - $<1.0 \times 10^4$
Adjustable	Easily adjustable to fit all personnel.
Quality Control	Each band is date and lot coded to total quality control and auditing
Elasticity	Expansion ratio 1.5:1
Snap/Size	4mm post snap for ground cord, tested to MIL STD 202 Method 101
Color	Black
Meets or Exceeds	DOD-HDBK-263, DOD-STD-1686, EOS/ESD Std. No. 1-1987, EN10015/1
UL Listed	File E 157590
Cord Assembly	
Cord	Heavy Duty, Lightweight construction of Single bundle. Cord Diameter: 0.06" Coil Diameter: 0.26"
Resistor	One megohm ($\pm 10\%$) resistor molded into snap connection
Ground Connection	Standard banana plug
Cord Extension	Working Length: 10 feet.
Tested	Provides over 100,000 bending cycles per EOS/ESD-S1.0-1987 procedures.

Specifications for the Q007B Common Point Ground

Dimension (in / cm)	L: 2.12 / 5.385 W: 0.9 / 2.286 D: 0.9 / 2.286
Weight (oz / g)	2.4 / 68
Case Material	Fire Retardant ABS
Color	Green
Configuration	3 standard banana jack inputs, Brass Grounding Pin, 2 FR ABS Spades

Specifications for the PGC-015G Green 15 Foot Ground Cord

Length (ft / meters)	15 / 4.6
Resistor	One megohm ($\pm 10\%$) resistor molded into snap connection
Color	Green

1072 Tower Lane, Bensenville, IL 60106 USA
Phone +1 (630) 238-8883 Fax +1 (630) 238-9717

www.prostatcorp.com

©2014 Prostat Corporation. All rights reserved. Prostat, Prostat Corporation, Qube and the Prostat logo are trademarks or registered trademarks of Prostat Corporation or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. Complying with all applicable copyright laws is the responsibility of the user. Prostat reserves the right to change, without notice, product offerings or specifications. Printed in U.S.A.

REV4: [7/07/16]-PPS292



Distributed by

Pro-Pack Materials Pte Ltd
The ESD & Cleanroom Specialist

No. 2, Bukit Batok Street 23, #08-05 Bukit Batok Connection, Singapore 659554. sales@pro-pack.com.sg (65) 6354 1511