

GZ-1800W-H: Network Router

of GZ-1800W ESD Monitor



GZ-1800W-H is a dedicated network router to be used with a GZ-1800W **proactive** ULV ESD monitor. It has 4 connection ports each of which can connect to a maximum of 32 GZ-1800W monitors. A maximum of 128 monitors can be connected to this Router. The Router contains an RJ45 port that can connect to a LAN through TCP/IP. A special high speed processing technique is used in the Router to provide high performance data processing and communication amongst networked monitors and the host PC-based network management software. All connections between GZ-1800W monitors and the router are carried out through wireless data signals.



SPECIFICATIONS:

Key Functions:	<ul style="list-style-type: none">x4 wireless ports for broadcasting inter-connection among monitorsEach wireless port supports connection up to 32 monitorsx1 RJ45 connection port for TCP/IP link to Local Area Network (LAN)Automatic connection detection; Independent hardware operation
LED:	x 6 tricolor LED
Electrical:	9~12V DC, 1A; wifi 433Mhz, 32 channels selectable
Mechanical:	L: 4 inches W: 3 inches H: 2.1 inches

MEGALIN Megalin Source International

• Address : 3F-6 No.81 Sec.1 Xintai 5th Road, Xizhi District, New Taipei City 22101, TAIWAN
• Tel : +886-2- 8698-4181 (Main) • Fax : +886-2-8698-4197 • E-mail : sales@megalinsource.com
China Offices : Shenzhen/Suzhou Tel: +86-755-277469232

v.202002

(©2020 Megalin Source International. All Rights Reserved.)



Distributed by

Pro-Pack Materials Pte Ltd
The ESD & Cleanroom Specialist

• No. 2, Bukit Batok Street 23, #08-05 Bukit Batok Connection, Singapore 659554. • sales@pro-pack.com.sg • (65) 6354 1511