

GZ-160x Single Workstation Monitor

GZ-160x is an extremely flexible, economical, continuous monitor series specifically designed for those price-sensitive customers. It is based on a unique, accurate, low-voltage, resistive loop detection technology and precision SMT manufacturing. It is able to attain various monitoring requirements to fulfill your strong need to meet all kinds of challenges



Models Selector Table:

Function \ Model	GZ-1601	GZ-1602	GZ-1603	GZ-1604
OPERATOR	v	v	v	v
ESD MAT		v	v	
TOOL			v	v

Features:

- ☒ Able to monitor operator, ESD mat and machine ground.
- ☒ Wrist-strap alarm: 35M/1.8MΩ, Table MAT alarm: 100MΩ, Machine alarm: 10Ω.
- ☒ 3-color LED to indicate status of operator wrist-strap: High, Low, Safe, Idle.
- ☒ Audio and LED will give alarms when monitor detects problems on grounding.
- ☒ Audio alarm volume is user adjustable with maximum of 85dB typical.
- ☒ Normal voltage when wearing wrist-strap is 100mV. Open wrist-strap: 0.9V.
- ☒ Maximum mat voltage : 900mV.
- ☒ Maximum machine voltage and current (Hard Grounding) : 50mV, 0.2mA.
- ☒ Human body voltage filtration.



Megalin Source International

(v.201903)

Address : 3F-6 No.81 Sec.1 Xintai 5th Road, Xizhi District, New Taipei City 22101, TAIWAN

• Tel +886-2- 8698-4181 (Main) • Fax : +886-2-8698-4197 • E-mail : sales@megalinsource.com

China Offices : • Shenzhen : +86-755-2774-6923 • Kunshan/Suzhou : +86-512-5519-7252

(©2019 Megalin Source International. All Rights Reserved.)



Distributed by

Pro-Pack Materials Pte Ltd

The ESD & Cleanroom Specialist

📍 No. 2, Bukit Batok Street 23, #08-05 Bukit Batok Connection, Singapore 659554. ✉ sales@pro-pack.com.sg ☎ (65) 6354 1511